

FCM

Fixed Curb Mounted Skylight

A non-vented, aluminium framed skylight. Used to bring natural light into rooms where ventilation is not required or where there is adequate ventilation. Specially suited to low roof pitches.



Frame

Aluminium Frame. Glazing unit siliconed into frame to suit low roof pitch applications.

Exterior capping Aluminium

Exterior colour Grey

0004 Glazing

Toughened, heat-stop Low-E coated laminated double glazing. Outer pane is a single 3mm toughened safety glass pane. The inner layer comprises two 2.5mm heat strengthened panes with a 0.76mm interlayer. 6mm Argon gas sealed space. Complies with AS1288.*

Performance

UV ray reduction:	99 %
Radiant heat reduction:	80 %
Noise reduction:	32 db

Energy rating

Fixed Curb Mounted Skylights have been energy rated in accordance with the Skylight Energy Rating Scheme (SERS).

5 out of 5 stars in Summer.

4.5 out of 5 stars in Winter.

4.5 out of 5 stars for Cool Daylight.

See separate sheet in these pages for further details.

Important considerations

- VELUX FCM Skylights can be used for low sloping roofs. The low profile external covering and glazing seal prevents water infiltration even at 0 degrees. However, to prevent water 'ponding' on the glass a minimum pitch of 3° - 5° is recommended.
- VELUX FCM does not come with a flashing kit but can be used with a variety of kerb flashings. Contact VELUX or an approved flashing manufacturer for more information.

FCM installation pitch: 0° - 60°

*Australian Standard 1288 stipulates laminated glass must be used in overhead glazing 3metres or more above floor level.