

April 2010

Light & Ventilation Data

MODEL		OVERALL FRAME SIZE (mm)	DAYLIGHT AREA (M2)	VENTILATION AREA (M2)
FS	C01	550 x 700	0.28	
	C04	550 x 980	0.41	
	C08	550 x 1400	0.61	
	M04	780 x 980	0.62	
	M06	780 x 1180	0.75	
	M08	780 x 1400	0.91	
	S01	1140 x 700	0.64	
	S06	1140 x 1180	1.15	
VS/VSE	C01	550 x 700	0.21	0.24
	C04	550 x 980	0.32	0.33
	C08	550 x 1400	0.49	0.44
	M04	780 x 980	0.51	0.39
	M06	780 x 1180	0.63	0.44
	M08	780 x 1400	0.77	0.50
	S01	1140 x 700	0.52	0.40
	S06	1140 x 1180	0.99	0.54
FCM*	2222	665 x 665	0.33	
	2234	665 x 970	0.50	
	2246	665 x 1275	0.67	
	2270	665 x 1885	1.02	
	3030	870 x 870	0.60	
	3046	870 x 1275	0.92	
	4646	1275 x 1275	1.39	
GGL/GHL	C02	550 x 780	0.22	0.32
	C04	550 x 980	0.27	0.38
	M04	780 x 980	0.44	0.57
	M06	780 x 1180	0.66	0.72
	M08	780 x 1400	0.70	0.86
GDL	P19			2.09
	Maximum opening (top & bottom elements)	940 x 2600		
	Top Element	940 x 1600	1.03	1.30
	Bottom Element	940 x 980	0.56	0.79

* FCM dimensions shown refer to overall throat (curb) dimension