

TWF & TWR

Tubular Sun Tunnel

A non-vented, tubular shaft sun tunnel. Used to bring natural light into rooms where it's not possible or appropriate to install traditional skylights or roof windows. Perfectly suited for small areas such as hallways or walk-in wardrobes. Available with flexible tube (TWF) or rigid shaft (TWR). Standard tunnel diameter is 350mm.



Frame

Maintenance free polyurethane with integrated flashing.

Exterior colour Dark Grey

Glazing

The Sun Tunnel has a single pane of 4mm clear, toughened glass incorporated into the frame. The glazing has been coated with an "easy clean" film to prevent dirt buildup. Simply hose with water to clean.

Performance

UV ray reduction:	n/a
Radiant heat reduction:	n/a
Noise reduction:	n/a

Light control

The Sun Tunnel is supplied with a ceiling diffuser to 'soften' the light. There are no blind or accessories available.

Important considerations

- The light output will vary depending on orientation, daylight conditions, length of shaft, time of day, etc.
- The flexible tube can be used to circumvent obstructions in the roof cavity but the rigid tunnel uses 2 x 45 degree elbows for most direct "line-of-sight" applications.
- Standard shaft lengths can be extended with the addition of the rigid extension kit ZTR 014. (1240mm in length)
- The glass is an integral part of the polyurethane frame and can only be cleaned from the outside.

Sun Tunnel installation pitch: 15° - 60°